



Part Number: GHT2619

Reed Switch – Standard - Normally Open Contacts

Product Data Sheet

PRODUCT	DIMENSIONS
---------	------------



Drawings not to scale. All dimensions in mm (inches)

SPECIFICATION		
CONTACT FORM		Form A (Normally Open)
CONTACT MATERIAL		Rhodium
SWITCHING CAPACITY	Max.	12 W/VA
SWITCHING VOLTAGE	Max.	230 V ac/dc
SWITCHING CURRENT	Max.	1.0A
CARRYING CURRENT	Max.	2.0A
DIELECTRIC STRENGTH	Min.	400Vdc
CONTACT RESISTANCE	Max.	100mΩ
INSULATION RESISTANCE	Min.	10 ¹¹ Ω
PULL-IN SENSITIVITY		30 – 50AT
DROP-OUT SENSITIVITY	Min.	5
BOUNCE TIME	Max.	0.5ms
RELEASE TIME	Max.	0.10ms
RESONANT FREQUENCY	Typ.	2900Hz
OPERATING FREQUENCY	Max.	200Hz
VIBRATION	10-1000	35g
SHOCK		50
CAPACITANCE	Typ.	0.5 pF
OPERATING TEMP. RANGE	Deg.	-40 +125 °C
TEST COIL	Type	1700

NOTE	ORDERING INFO
- When cutting or bending switch leads it is important that the glass seal is not damaged. The cutting or bending point should be no closer than 3mm (0.118in.) to the glass to metal seal and the lead should be supported between the cutting or bending point and the glass to metal seal. - We offer a crop and form service for Reed Switches to be customized to your specification.	PART NUMBER GHT2619 30 50 - Type - Minimum (AT) Sensitivity - Maximum (AT) Sensitivity

Made in India